



3.5kw 16A Type1 Homeuse Portable EV Charger AC Fast Mobile EV Charger Station With Plug Protection

Our Product Introduction

for more products please visit us on evstationcharger.com

Basic Information

- Place of Origin: China
- Brand Name: MINKO
- Certification: CE(ICR lab), UKCA, ROHS ISO, REACH
- Model Number: UPC-62-16AC
- Minimum Order Quantity: 5 pieces
- Price: negotiation
- Packaging Details: L210xW85xH52 (mm)
- Delivery Time: 8 -10 working days
- Payment Terms: T/T, Western Union, MoneyGram, Paypal, Skrill, Transferwise
- Supply Ability: 1000000 pieces per month




Product Specification

- Charging Plug: SAE J1772 Type 1
- Rated Voltage: AC 110-240V
- Rated Current: 16A
- Rated Power: 3.5kW
- Input Power: 250V Max
- Operating Temperature: -35°C To 50°C
- Start Method: Plug And Play
- Electric Cable: IP65 Circuit Breaker
- Highlight: **3.5kw Type 1 Charging Station, Type 1 Charging Station 240vac, type 1 car charger 16a**



More Images



Product Description

3.5kw 16A Type1 Homeuse Portable EV Charger AC Fast Mobile EV Charger Station with Plug Protection

Detailed specification:

Portable EV Charger, with power ratings of 3.5KW, 7 kW, is suitable for different types of vehicles.

Adjustable current, suitable for various scenarios.

The Voltage and Current are stable during charging, which can protect the battery and delay using time.

We can use normally in ultra-high temperature environment up to 50 .

It can also be used normally in the -35 .

Charging plug	SAE J1772 Type 1
Model No.	UPC-62-16AC
Rated voltage	AC 110-240V
Rated current	16A
Rated power	3.5kW
Certificates	CE(ICR lab), UKCA, ROHS,ISO, REACH
Protection rank	IP54 cable; IP65 circuit breaker
electric cable	IP65 circuit breaker
LCD	2.8" LCD screen
LED indicator	Blue/Red/Green
Earth leakage protector	30m AC
input power	250V Max
length	5m or customized
Package Size	L210xW85xH52 (mm)
start method	Plug and Play
Operating temperature	-35°C to 50°C
electrical protection	Overcurrent protection, residual current protection, grounding protection, surge protection, Overvoltage/undervoltage protection, overvoltage/underfrequency protection, overtemperature protection
Applied Materials	Housing: Black thermoplastic PC940. Corrosion and wear protection. Cable: 4.5M black with TPU jacket. With CE and TUV mark issued by TUV.
Feature	1. The product complies with the Low Voltage Directive 2014/35/EU, IEC61851-1:2019 2.IP67, weatherproof; leakage protection; impact resistance 3. Charging status and working error are simply displayed by LED indicator light and LCD screen 3. Optional function of current selection button, 4.8A-32A free switching current
Warranty	1 Years for the whole machine

Advanteages:

Temperature Protection

Efficient Charging

Short Circuit Protection

Protection Level IP66

Built in Smart Chip



Temperature Protection



Efficient Charging



Short Circuit Protection



Protection Level IP66



Built in Smart Chip

Product details



Customizable plug



Customizable



Simple and easy to operate



EV CHARGING



Easy to carry and charge



Packing list

Packing list

**Caution:**

Don't submerge the EV charging cable in water.

Don't step on, fold or knot the cable.

Don't drop the EV charging box or place a heavy object on it.

Don't place the charging cable near high temperature object when charging.

Don't operate the EVSE in temperatures beyond its operating range of -25°C to 55°C.

Power-supply side input cable should be at least 3*2.5mm (recommended 3*4mm), with a standard 16A socket. It is suggested that

the power distribution is done by the professionals.

Don't put fingers into the charging connector when the power plug is still connecting to the power.

Don't use this EV charging box when the cable is damaged.

The EV charging box is only for EV charging using.

Don't use this device with other brand's extension cord or adapter.



MINKO (SZ) TECHNOLOGY CO., LIMITED



+8613539872669



yumiko@szminko.com



evstationcharger.com

309 West Lake Industrial Zone, Cuishan Road, Dongxiao Street, Luohu District, SZ